



**Lighting system**  
Optic: Ledil lenses 120°  
High brightness power LEDs  
Lifetime: 50 000 h (L-70)

**Applications**  
Outdoor places,  
streetlighting

**Features**


- Passive cooling
- Mounting pole: Ø42 - 60mm
- Meets CE safety standards
- Diecast alu and polimer body
- Tempered glass face
- Protection rating: IP66, IK08



Ordering Code	Product Name	Light Output [lm]	CRI	System Power [W]	Color Temp. [K]	Power Supply [V]	Weight [Kg]
300 763	LT-SOL Kombo 15-23/74	2 324	>70	14,98	4 000	230 AC	4
300 764	LT-SOL Kombo 25-38/74	3 806	>70	23,99	4 000	230 AC	4
300 778	LT-SOL Kombo 40-56/74	5 643	>70	37,68	4 000	230 AC	4,2
300 779	LT-SOL Kombo 55-83/74	8 310	>70	56,55	4 000	230 AC	4,5
301 017	LT-SOL Kombo 75-112/74	11 236	>70	76,62	4 000	230 AC	4,7
301 028	LT-SOL Kombo 95-132/74	13 197	>70	95,12	4 000	230 AC	4,7




adjustable in: -10, -5, 0, +5, +10 angle



sizes



easy mounting system



cd/klm: c0-180 c90-270