

BREEZ

Felületre szerelhető érzékelős
LED lámpatest
Surface Mounted Sensored
LED luminaire

SZERELÉSI ÚTMUTATÓ

A lámpatest telepítését és karbantartását csak képzett szakember végezheti! Kérjük, vegye figyelembe a LED fényforrás élettartamára vonatkozó előírásokat! Sérült üveget azonnal ki kell cserélni! A garancia azonnal érvényét veszti, ha a vevő a lámpatesten a gyártó előzetes engedélye nélkül bármilyen módosítást végez! Szakszerűtlen felszerelésből vagy extrém üzemeltetési körülményekből származó meghibásodás esetén a garancia érvényét veszti!

A szerelési útmutatót kérjük, őrizze meg!

MAXIMÁLIS KÖRNYEZETI HŐMÉRSÉKLET 35 °C 

INSTALLATION INSTRUCTION

The luminaire may only be installed and maintained by qualified technicians! Please pay attention to LED light-source lifetime! The damaged or broken glass must be replaced immediately!

Any modifications of the luminaire structure without supplier's permission can end product guarantee! In case of any failure caused by unprofessional installation or operating under extreme conditions the product may end!

Please retain these instructions for later reference!

MAXIMUM AMBIENT TEMPERATURE 35 °C 

Installation Procedure

WARNING


1. Switch off before installation / maintenance.
2. Switch on only after complete installation and examination of the circuit.
3. Professional electrician for installation and maintenance only.



Turn Off power supply before starting any installation. Read instructions & check you have all the tools & accessories to complete the installation correctly.


Surface mounted Installation

Step1



Take out ceiling light and accessory pack from box


Step2



Take rubber stopper out from slide switch for color selection.


Step3

/optional/



Choose color by slide switch with correspond color temperature.

Step4




Insert rubber stopper back into slide switch properly.

Step5



Knock-in the plastic anchor into ceiling

Step6




Remove screw, take out bracket

Step7



Fix bracket with screw into the ceiling

Step8




Open junction box, wire "L" "N" to terminal block and mount ceiling light into the right place

— L=LIVE
— N=NEUTRAL

Step9

Switch on



301053
301056
301260
301274
301275

IK10 **LED** IP54

